

**Product Datasheet Safety Helmet pheos B
with three variable ventilation zones**



UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth

<p>Product characteristics</p>	<ul style="list-style-type: none"> * size and weight optimised helmet * trendy design * variable air vents at the front and the back of the helmet * optimal fit, high wearing comfort * 6-point textile suspension harness optionally with wheel ratchet system * approved and labeled for use in temperatures as low as -30°C * approved and labeled for Molten Metal * Adapter systems for uvex visors, uvex earmuffs and lamps with helmet attachment * suitable for head sizes of 51-61 cm resp. 52-61 cm (wheel ratchet system) * large printing areas
---------------------------------------	---

Technical details	
Helmet shell	
Material	PE
Weight	ca. 296 g
Interior	<ul style="list-style-type: none"> * 6-point-textile suspension harness * headband made of high quality PE * circulating pad * easy to replace sweatband * medically shaped neck band to prevent slide on overhead working
Versions	Conventional suspension harness
Weight	ca. 86 g
Colours / Art. No.	white 9772 020 yellow 9772 120 orange 9772 220 red 9772 320 blue 9772 520 black 9772 920
	Suspension harness with wheel ratchet system for infinite width adjustment
Weight	ca. 98 g
Colours / Art. No.	white 9772 030 yellow 9772 130 orange 9772 230 blue 9772 530
Packing	25 pieces / box
Standards	DIN EN 397 in combination with EG-guideline 89/686/EWG with additional requirements for - “very low temperature” -30° C - “Molten Metal”