SAFECO

SAPEMA

SABS An SABS ISO 9001 Quality Management System certified company
ISO 9001

INDUSTRIAL SAFETY CAP - PEAKED BRIM

PROUDLY MADE IN SOUTH AFRICA

SABS APPROVED

SABS SANS 1397

the dme
Department: Mineral and Energy
REPUBLIC OF SOUTH AFRICA

GME Approved
HH 2006-03-07
HH 2006-03-08

PRODUCT DESCRIPTION

- Safeco industrial safety cap
- Peaked brim
- 6 Point suspension harness
- 3 harness options: standard, ratchet plastic & ratchet webbing
- SABS SANS 1397 compliant
- 17 Standard colours

TECHNICAL SPECIFICATIONS

- High impact resistant shell.
- Assembled weight: Standard harness 284g, plastic ratchet harness 306g, webbing ratchet harness 300g
- One size fits all
- 6 Point suspension harness attachment
- Harness nape strap adjustment from 50cm to 64cm. Available in the following:
  - a. 6 pin buckle fastener
  - b. Auto-locking ratchet
  - c. Auto-locking ratchet and webbing
- 40mm Peaked brim
- 270^{0} Gutter
- 2 Accessory slots
- 3 Lugs for chinstraps
- 2 Year UV stabilised shell
- Materials: Poly Propylene (PP) Shell, Poly Ethylene (LLDPE) 2-part harness, Tricot foam cushion sweatband
- Shell colours: White, Royal Blue, Yellow, Orange, Red, Green, Lime, Grey, Sasol Blue, Bright Pink, Hi Viz Lemon, Sun Yellow, Maroon, Brown, Purple, Navy and Black
- Harness colour: Natural
- Sweatband colour: Black

COMPLIANCE

- SABS Mark certification: 4886/12692
- SANS 1397:2003 standard compliant
- Department of Minerals and Energy GME Approved
  - HH 2006-03-07
  - HH 2006-03-08
- 440 VAC insulated
- Proudly made in South Africa

PACKAGING

- Standard harness:
  - 20 assembled per clear bag 75cm x 55cm x 24cm x 5.8kg
  - 40 assembled per woven export bag 140cm x 55cm x 24cm x 11.6kg
- Plastic ratchet harness:
  - 10 assembled per clear bag 56cm x 55cm x 24cm x 3kg
  - 30 assembled per woven export bag 168cm x 55cm x 24cm x 9.8kg
- Webbing ratchet harness:
  - 10 assembled per clear bag 56cm x 55cm x 24cm x 3kg
  - 30 assembled per woven export bag 168cm x 55cm x 24cm x 9kg

INSTRUCTIONS

To provide protection the helmet must be fitted correctly and harness adjusted to the size of the users head. One size fits all, adjustable headband 50cm-64cm. Storage must be provided in a cool clean environment away from harmful ultra-violet light exposure. Do not stack more than 6 rows horizontally on top of each other. Do not stack any objects on top. Packaging for bulk handling should be in clear PE bags, woven bags or boxes. Date of issue must be recorded on this label in the space provided. Recommended shelf life: 24 months. Recommended period of use from date of issue: 12 months. Or as otherwise considered necessary by safety officer, representative or specified requirements.

WARNING

This helmet provides limited protection to the upper head against falling objects and impacts and is designed to absorb the energy of an impact by partial destruction or damage to shell, harness and/or both. Although damage may not be apparent, helmets subjected to an impact should be replaced immediately. Components of the helmet should not be removed/modified/adapted to a purpose or to fit attachments in any way. Inspect and maintain the helmet and harness on a regular basis. Replace damaged or worn harness immediately. Only use SAFECO replacement harness. Application of solvents, aerosols, paint, petroleum products and/or cleaning agents may cause damage to the helmet. Only use a solution of mild soapy water to clean the helmet.

COLOURS

INDUSTRIAL SAFETY CAP - SHORT BRIM

PRODUCT DESCRIPTION

- Safeco industrial safety cap
- Short brim
- 6 Point suspension harness
- 3 harness options: standard, ratchet plastic & ratchet webbing
- SABS SANS 1397 compliant
- 6 Standard colours

TECHNICAL SPECIFICATIONS

- High impact resistant shell.
- Assembled weight: Standard harness 278g, plastic ratchet harness 300g, webbing ratchet harness 294g
- One size fits all
- 6 Point suspension harness attachment
- Harness nape strap adjustment from 50cm to 64cm. Available in the following:
  - a. 6 pin buckle fastener
  - b. Auto-locking ratchet
  - c. Auto-locking ratchet and webbing
- 20mm Peaked brim
- 270^0 Gutter
- 2 Accessory slots
- 3 Lugs for chinstraps
- 2 Year UV stabilised shell
- Materials: Poly Propylene (PP) Shell, Poly Ethylene (LLDPE) 2-part harness, Tricot foam cushion sweatband
- Shell colours: White, Royal Blue, Yellow, Orange, Red, Green, Lime, Grey, Sasol Blue, Bright Pink, Hi Viz Lemon, Sun Yellow, Maroon, Brown, Purple, Navy and Black
- Harness colour: Natural
- Sweatband colour: Black

SABS APPROVED

SABS SANS 1397

the dme

GME Approved
HH 2006-03-07
HH 2006-03-08

COMPLIANCE

- SABS Mark certification: 4886/12692
- SANS 1397:2003 standard compliant
- Department of Minerals and Energy GME Approved
  - HH 2006-03-07
  - HH 2006-03-08
- 440 VAC insulated
- Proudly made in South Africa

PACKAGING

- Standard harness:
  - 20 assembled per clear bag 75cm x 55cm x 24cm x 5.8kg
  - 40 assembled per woven export bag 140cm x 55cm x 24cm x 11.6kg
- Plastic ratchet harness:
  - 10 assembled per clear bag 56cm x 55cm x 24cm x 3kg
  - 30 assembled per woven export bag 168cm x 55cm x 24cm x 9.8kg
- Webbing ratchet harness:
  - 10 assembled per clear bag 56cm x 55cm x 24cm x 3kg
  - 30 assembled per woven export bag 168cm x 55cm x 24cm x 9kg

INSTRUCTIONS

To provide protection the helmet must be fitted correctly and harness adjusted to the size of the users head. One size fits all, adjustable headband 50cm-64cm. Storage must be provided in a cool clean environment away from harmful ultra-violet light exposure. Do not stack more than 6 rows horizontally on top of each other. Do not stack any objects on top. Packaging for bulk handling should be in clear PE bags, woven bags or boxes. Date of issue must be recorded on this label in the space provided. Recommended shelf life: 24 months. Recommended period of use from date of issue: 12 months. Or as otherwise considered necessary by safety officer, representative or specified requirements.

WARNING

This helmet provides limited protection to the upper head against falling objects and impacts and is designed to absorb the energy of an impact by partial destruction or damage to shell, harness and/or both. Although damage may not be apparent, helmets subjected to an impact should be replaced immediately. Components of the helmet should not be removed/modified/adapted to a purpose or to fit attachments in any way. Inspect and maintain the helmet and harness on a regular basis. Replace damaged or worn harness immediately. Only use SAFECO replacement harness. Application of solvents, aerosols, paint, petroleum products and/or cleaning agents may cause damage to the helmet. Only use a solution of mild soapy water to clean the helmet.

COLOURS

SAFECO

SAPEMA SABS An SABS ISO 9001 Quality Management System certified company

SAFETY CAPS ATTACHMENTS & ACCESSORIES

PLASTIC LAMP BRACKET & CABLE CLIP

- Red Poly Propylene (PP) lamp brackets & cable clip.
- Fastened with nickel-cadmium rivets.
- Does not provide VAC 440 insulation

METAL LAMP BRACKET & CABLE CLIP

- Electroplated mild steel lamp bracket
- Red Poly Propylene (PP) cable clip
- Fastened with nickel-cadmium rivets
- Does not provide VAC 440 insulation

2 POINT CHIN STRAPS

- 2 point hook attachment
- Reusable ball and clasp release system
- Anti twist design
- 15mm webbing strap
- Double slide adjustment
- Optional chin cup

3 POINT CHIN STRAPS

- 3 point lug attachment
- 4 part assembly
- Quick release curved buckle
- 16mm webbing straps
- Double slide adjustment
- Optional chin cup

SAFECO

SAPEMA SABS An SABS ISO 9001 Quality Management System certified company

REPLACEMENT HARNESS

STANDARD HARNESS

- 6 point suspension harness
- 2 stage height adjustment
- Nape strap adjustment from 50cm to 64cm
- 6 pin buckle fastening nape strap
- 2 part Poly Ethylene (LLDPE) harness
- Tricot foam cushion sweatband

RATCHET PLASTIC HARNESS

- 6 point suspension harness
- 2 stage height adjustment
- Nape strap adjustment from 50cm to 64cm
- Auto locking ratchet
- 2 part Poly Ethylene (LLDPE) harness
- Poly Propylene (PP) ratchet
- Tricot foam cushion sweatband

RATCHET WEBBING HARNESS

- 6 point suspension harness
- 2 stage height adjustment
- Nape strap adjustment from 50cm to 64cm
- Auto locking ratchet.
- 7 part Poly Ethylene (LLDPE) liner
- 25mm webbing harness
- Poly Propylene (PP) ratchet
- Tricot foam cushion sweatband

SAFECO

SAPEMA

SABS ISO 9001 An SABS ISO 9001 Quality Management System certified company

BRANDING OPTIONS

EMBOSSING

- Full in-house embossing service
- Accurate and consistent logo reproduction
- Up to 5 colour prints
- Front, left, right and back positioning
- Solvent based inks and heat treatment ensure a long lasting and durable print

VINYL STICKERS

- Full in-house digital printing & graphic design service
- Accurate and consistent logo reproduction
- Unlimited colour prints
- Front, left, right and back positioning
- Solvent inks printed on white and silver reflective vinyl